

# FLIR MILSIGHT® S135 MUNS™



## AN/PVS-27 Magnum Universal Night Sight

The MilSight® S135 MUNS™ clip-on weapon sight allows snipers to detect and recognize man-size targets in excess of 1,500 meters. The S135 MUNS is engineered for battlefield use, successfully tested on weapons up to and including .50 caliber.

### FEATURES

- Compatible with Standard Sight
- Multi-use design
- Optimized for medium and long-range sniper weapons
- Built-in image intensifier protection for added longevity
- Small and lightweight
- Simple operation
- No special batteries required

### BENEFITS

- Designed to mount on any MIL-STD-1913 rail interface forward of an existing scope, adding night vision capabilities to target acquisition platforms
- Offers mission flexibility as a high-resolution night vision weapon sight, mounted on a spotting scope for long range reconnaissance, hand-held as an observation device.
- Effective on all weapons from carbines to .50 caliber semi- automatic and bolt action sniper rifles, including the M110, SR-25/MK11, XM107, .338 Lapua, .308 M24, Chandler & .300 Win Mag
- Includes FLIR's proprietary Shock Mitigation System™ (SMS™), allowing the unit to be used on weapons up to and including .50 caliber bolt-action rifles
- Highly portable design reduces operator fatigue
- Large, rugged controls for basic image adjustment, no complicated menus to navigate
- Runs on common AA batteries



Milsight® S135 MUNS™ Sniper deployment

### APPLICATIONS

- Target Acquisition
- Reconnaissance
- Covert Operations
- Surveillance
- Special Law Enforcement

## Specifications

SYSTEM CHARACTERISTICS	
Magnification	Unity
Optimum Dayscope Magnification	3X to 20X
Focus Range	15 m to Infinity
Field of View	10°
I <sup>2</sup> TUBE FEATURES	
Tube Type	Gen III, Autogated
Tube Color	Green Phosphor
Tube Performance	1800 FOM Typical
Resolution	64 Line Pair
BORESIGHT CHARACTERISTICS	
Accuracy	Factory Aligned to 1 MOA or Better
Adjustments	None
Repeatability	Within 1 MOA
PHYSICAL CHARACTERISTICS	
Shock Mitigation System™ (SMS™)	.50 Caliber BMG Qualified
Operating Temperature	-30° to +60° C
Submersion	33 ft.
Interface (to MIL-STD 1913)	LaRue Adjustable Double Locking Lever Mount
DIMENSIONS, WEIGHT & MOUNTING	
Interface	Double Locking Levers (MIL-STD 1913, Picatinny Rail)
Length	8.7 in
Weight (w/o batteries)	50 oz
Max Height Above Rail	3.75 in
INTERFACES	
Controls	On/Off/Gain, Focus
Power	2 AA
OPTICAL CHARACTERISTICS	
Objective Lens Focal Length	92 mm
Objective Lens f/Number	f/1.0
Output Optic Exit Pupil Diameter	40 mm
PERFORMANCE OPTIONS*	
Tube Color	Green or White Phosphor
Available FOM*	2000, 2200, >2200
Resolution	72 line pair/mm

\*Note: system performance and tube specifications are ITAR controlled for export outside the United States. Availability of all image intensified systems for sale outside the US are subject to US State Department approval. The highest Figure of Merit (FOM) will be stated as LIMITED (maximum) for export



Milsight® S135 MUNS™

**CORPORATE HEADQUARTERS**  
 FLIR Systems, Inc.  
 27700 SW Parkway Ave.  
 Wilsonville, OR 97070  
 PH: +1 877.773.3547

**SANTA BARBARA**  
 FLIR Systems, Inc.  
 6769 Hollister Ave.  
 Goleta, CA 93117  
 PH: +1 805.690.6602

**MIDDLE EAST**  
 Suite 1-11  
 Building 6E-A  
 Dubai Airport Freezone  
 PO Box 371363  
 Dubai, UAE  
 T +971 4 701 7195  
 F +971 4 701 7194

**EUROPE**  
 FLIR Systems, Inc.  
 Luxemburgstraat 2  
 2321 Meer  
 Belgium  
 PH: +32 (0) 3665 5100

www.flir.com  
 NASDAQ: FLIR



EXPORT

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2017 FLIR Systems, Inc. All rights reserved. 05/10/17

17-1527-SUR-LND